

All the **cooling** you want.

₱1/HR
cost-to-run

Based on an 8-hour run test
at 18°C for 1.0HP only.

UPGRADE TO THE
NEW **Carrier** AURA





AURA



Based on an 8-hour run test at 18°C for 1.0HP only.

Costs almost nothing to operate with **Energenius Inverter Technology** and **Full Direct Current Technology**.



Includes Eye Sensor that automatically **reduces energy use** when you're not in the room.



Keep the remote with you and it **cools the area where you're at** with your desired temperature.

AURA INVERTER SPLIT			1.0HP	1.5HP	2.0HP	2.5HP
Set Code			53CEP009308-1	53CEP012308-1	53CEP018308-1	53CEP024308-1
Indoor			42CEP009308-1	42CEP012308-1	42CEP018308-1	42CEP024308-1
Outdoor			38CEP009308-1	38CEP012308-1	38CEP018308-1	38CEP024308-1
Power supply			V-Ph-Hz	230-1-60	230-1-60	230-1-60
Cooling (Standard conditions)	Capacity	kW	2.78 (0.78 - 3.61)	3.61 (0.78 - 4.58)	5.42 (0.79 - 5.97)	7.22 (1.67 - 9.17)
		kJ/Hr	10,000 (2,800 - 13,000)	13,000 (2,800 - 16,500)	19,500 (2,850 - 21,500)	26,000 (6,000 - 33,000)
	Power Input	W	500 (170 - 850)	800 (170 - 1,375)	1,180 (130 - 1,450)	1,620 (235 - 2,490)
	CSPF	-	7.82	7.28	7.24	7.39
	Star rating	-	5	5	5	5
	Current	A	2.4 (1.1 - 4.1)	3.6 (1.1 - 6.1)	6.4 (1.6-6.9)	7.3 (2.0 - 11.0)
Safety	Rated Power Input (based on IEC 60335-2-40)	W	2005	2005	2650	4055
	Rated Current (based on IEC 60335-2-40)	A	9.0	9.0	13.0	18.0
Compressor	Type	-	Rotary Inverter	Rotary Inverter	Rotary Inverter	Rotary Inverter
Indoor fan motor	Model		BLDC	BLDC	BLDC	BLDC
	Speed (Hi/Mi/Lo)	rpm	1000 / 850 / 780	1000 / 850 / 780	1150 / 970 / 880	1000 / 850 / 760
Indoor unit	Dimension (W*D*H)	mm	795 * 225 * 295	795 * 225 * 295	965 * 239 * 319	1140 * 275 * 370
	Packing (W*D*H)	mm	870 * 370 * 305	870 * 370 * 305	1045 * 400 * 325	1230 * 455 * 355
	Stacking Height		8	8	8	8
	Net/Gross weight	kg	10.0 / 12.5	10.0 / 12.5	12.0/16.0	18.0/22.5
Outdoor fan motor	Model		BLDC	BLDC	BLDC	BLDC
	Speed	rpm	800 / 560	800 / 560	850 / 550	850 / 550
Outdoor unit	Dimension (W*D*H)	mm	765 x 303 x 555	765 x 303 x 555	805 x 330 x 554	890 x 342 x 673
	Packing (W*D*H)	mm	887 x 337 x 610	887 x 337 x 610	915 x 370 x 615	995 x 398 x 740
	Stacking Height		4	4	3	3
	Net / Gross weight	kg	24.0 / 26.0	24.0 / 26.0	28.0 / 31.0	37.0/40.0
Refrigerant type	type/kg		R32 / 0.45	R32 / 0.45	R32 / 0.71	R32 / 1.1
Refrigerant piping	Maximum refrigerant pipe length	m	25	25	30	40
	Additional refrigerant	g/m	12	12	12	12
	Max. difference in level	m	10	10	20	25
	Liquid side	mm(in)	6.35mm(1/4in)	6.35mm(1/4in)	6.35mm(1/4in)	6.35mm(1/4in)
	Gas side	mm(in)	9.52mm(3/8in)	9.52mm(3/8in)	12.7mm(1/2in)	12.7mm(1/2in)

NOTES:

- Capacity rating is based on the following standard conditions:
Indoor condition: 27 °C DB / 19 °C WB
Outdoor condition: 35 °C DB / 24 °C WB
- Product information and specifications in the brochure have been obtained under specific testing conditions and are applicable to the data publication only.
- Product information and specifications are subject to change without notice due to continuous product development and improvement.
- Concepcion-Carrier Air Conditioning Company (CCAC) does not warrant the accuracy of all product information and specifications contained herein.
- CCAC shall not be liable for any claim of error, omission, or misrepresentation in relation to the information and specifications contained herein, or for any loss or damage from reliance on such information or specification.



Enjoy 1-year warranty on parts and service, 3 years on PCB, and up to 10 years on the compressor.



HEAD OFFICE
KM 20 East Service Road,
South-Superhighway,
Muntinlupa City, Philippines

CUSTOMER CARE HOTLINE
(02) 88635555

— The Air Authority —

VISIT OUR WEBSITE



carrier.com.ph