


## AIR CONDITIONING REDEFINED Quick, quiet, cost-efficient cooling at its sleekest.

# AIRCONDITIONING REDEFINED

Reinvent any experience with Carrier Slim's energy-efficient cooling system. Its 3D airflow distribution creates a refreshing atmosphere without direct drafts, ensuring every moment is enjoyed in perfect comfort.





#### **MODERN & SLEEK DESIGN, MINIMAL FOOTPRINT**

Instantly upgrade interiors and optimize every space with Carrier Slim — the smallest footprint in its class.



#### SUPERIOR ENERGY EFFICIENCY

Enjoy cooling comfort with minimal impact on your bottom line. Carrier Slim has the highest CSPF rating in its category and 5-Star Energy Rating<sup>\*</sup>. Experience efficient cooling at only PHP 7.00 per hour.



QUIET LIKE A WHISPER AT 35 dB

Carrier Slim delivers powerful cooling at an ultra-quiet 35 dB, allowing you to stay focused, relax, or enjoy conversations without disruption.



#### QUICK, EVEN COOLING

With Carrier Slim's Breeze Away function, everyone can experience the unique 3D airflow distribution that evenly cools and envelops the room.



ACTIVE IONIZER FOR CLEAN AIR Enjoy cleaner, cooler air using Ion Cloud technology that eliminates bacteria and allergens, providing a healthier dining environment.



**TOOL-FREE MAINTENANCE** 

Carrier Slim's tool-free filters make it easier to clean. Plus, get reliable support with nationwide service and parts availability.



#### **BUILT TO ENDURE**

Protect the unit against rust and corrosion with a premium Gold Fin Anti-Corrosion Coating, ensuring long-lasting performance even with the Philippines' demanding climate.

### **Technical Specifications**

		1001000000
SET Code		1801000892
Model Code		53CLV036308
Capacity	kJ/hr	36,400 (7,200 - 39,000)
Capacity	kW	10.10 (2.00 - 10.80)
Power	W	3,400 (350 - 3,850)
EER	kJ/W-hr	10.70 (20.57- 10.13)
CSPF / Star Rating		6.15 / 5 Star
Electrical Char.	Volts-Ph-Hz	230-1-60
Rated Current	Amperes	22
Fan Coil Unit		
Fan airflow@High Speed	m3/hr	1,500
Sound Level (H/M/L/Silence)	dB(A)	49/44/41/35
Condensing Unit		
Sound Level	dB(A)	61
Refrigerant Type		R-32, 1.4kg
Ref. Pipe Size, (L/G)	mmØ	6.35 / 12.7
Max. Pipe Run	m	35
Max. Vertical Separation	m	10
FCU Dimensions		
Net Dimensions, W*H*D	mm	380 x 1,802 x 392
Gross Dimensions, W <sup>*</sup> H <sup>*</sup> D	mm	2,040 x 475 x 490 (Flat)
Weight, Net/Gross	kg	25.7/33.4
CDU Dimensions		
Net Dimensions, W <sup>*</sup> H <sup>*</sup> D	mm	946 x 810 x 420
Gross Dimensions, W <sup>*</sup> H <sup>*</sup> D	mm	1,090 x 885 x 500
Weight, Net/Gross	kg	51.9/ 56.0
Stacking Height, FCU/CDU		5/2

#### Notes:

1. Capacity rating is based on the following standard conditions: Outdoor Condition: 35°C DB / 24°C WB

Indoor Condition: 27°C DB / 19°C WB

2. Airflow is measured in dry conditions.

- Product information and specifications in the brochure have been obtained under specific testing conditions and are applicable to the data publication only.
- 4. Product information and specifcations are subject to change without notice due to continuous product development and improvement.
- 5. Concepcion Carrier Air Conditioning Company (CCAC) does not warrant the accuracy of all product information and specifications contained herein.
- 6. CCAC shall not be liable for any claim of error, or misrepresentation in relation to the information and specifications contained herein, or for any loss or damage resulting from reliance on such information or specification.

### CONCEPCION-CARRIER AIR CONDITIONING COMPANY

#### **Head Office**

Km 20 East Service Road, South Superhighway, Alabang, Muntinlupa City, 1771

#### **Regional Office**

Meerea High Street, Ouano Avenue, North Reclamation Area, Mandaue City, Cebu

### Customer Care Hotline (02) 88635555

Website carrier.com.ph

Socials Carrier Philippines

#### **VISIT OUR WEBSITE**



